

RG 6 / U-4


KOAKSİYEL KABLoları COAXIAL CABLES

YAPISI / CONSTRUCTION



STANDARD
MIL-C-17

- 1 İLETKEN / CONDUCTOR
1,02 mm Cu
- 2 YALITKAN / INSULATION
Köpüklü PE / foam PE
- 3 EKran 1 / SCREENING 1
Al folyo / Al foil
- 4 EKran 2 / SCREENING 2
SnCu örgü / SnCu braiding
- 5 DIŞKILIF / JACKET
PVC beyaz / white



TEKNİK VERİLER / TECHNICAL DATA

1. EMPEDANS / IMPEDANCE
75 ± 2
2. KAPASİTE / CAPACITANCE
57 pF/m
3. YAYILMA HIZI / VELOCITY RATIO
0,78
4. ÇALIŞMA SICAKLIĞI / TEMP RANGE
-40 / +70 °C
5. TEST GERİLİMİ / TEST VOLTAGE
1,2 KV
6. ZAYIFLATMA / ATTENUATION
100 MHz 7 dB
200 MHz 10 dB
500 MHz 17 dB
800 MHz 21 dB

- RG6/U4 Kapalı alanlarda CCTV, TV ve uydu anten sistemlerinde ses ve görüntü almak için kullanılır.
- RG6/U4 This coaxial generally used in CCTV systems, TV-satellite connections for audio and video transmission. Not suitable for outside use.

SİPARİŞ BİLGİLERİ / ORDERING DATA

AMBALAJ MİKTARLARI / SPOLL SIZES : 100-200-500-1000 mt